

INSPIRATIONS® POINT-OF-USE

MODELS

HOT & COLD: 360129 - BLACK

360130 - WHITE

COOK & COLD: 360127 - BLACK

360128 - WHITE

Features

- High quality, high output refrigeration and heating systems
- Same internal components as the Reflections® family
- Solid, one-piece cabinet made from High Density Polyethylene is extremely durable and easy to clean
- No external base plate
- Energy Star rated 2.0L hot tank with On/Off switch
- Stainless steel cold reservoir
- Removable, two-piece, dishwasher safe drip tray
- Dual mechanical float for reliability
- Available in black or white
- UL certified

MTN Model Numbers: H&C: IB215, IW215 C&C: IB115, IW115



IW 215



H&C: 360129 - B, 360130 - W C&C: 360127 - B, 360128 - W

Power	
Voltage (V)	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.44A / 118W / 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (KWH/24hrs)	1.14
% lower than ES Standard	5.0%
Hot Water System	
Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On)	166.57°F / 191.43°F
Hot water ARI Rating	45 6oz > 165°F +/- 10%
Hot Thermostat / Heat Limiter	203°F +/-5.5°F
Hot Thermostat / Thermister Cycle	167°F +/-11°F / 187°F +/-4°F
i-Boil Set Point	N/A
Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On)	N/A
Hot Water Flow Rate	0.96 oz/sec
Hot Water Flow Rate (oz per sec)w/Accu-Temp delay	N/A
Hot Tank Size (L)	2.0L
Heat Band Wattage	450W
Cold Water System	
Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON)	45.87°F / 42.2°F
Cold Water ARI Rating	27 5oz < 50°F +/-10%
Cold Thermostat Set Point	45°F +3°/-8°F
Cold Water Flow Rate	1.4 oz/sec
Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay	N/A
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal.)	1 / 0.55 / 0.4 G
Weights and Measurements	
Net Weight (H&C / C&C Lbs.)	34.6 / 31.68
Gross Weight (H&C / C&C Lbs.)	37.9 / 34.98
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.4x13.5x39 / 13x13.9x40
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	UL



Revised 2/1/2012