

INSPIRATIONS® LX

POINT-OF-USE

MODELS:

HOT & COLD: 360131 -BLACK
360132 -WHITE

COOK & COLD: 360133 -BLACK
360134 -WHITE

Features

- Same internal components as the Reflections® family
- HDPE cabinet with upgraded ABS
- EZ Replace front panels
- Integrated cup dispenser
- No external base plate
- Energy Star rated 2.0L hot tank with On/Off switch
- Stainless steel cold reservoir
- Removable, two-piece, dishwasher safe drip tray with slide out extension for larger containers
- Dual mechanical float for reliability
- Available in black or white
- UL listed

MTN Models Numbers:

H&C: IB215LX, IW215LX

C&C: IB115LX, IW115LX



IB 215 LX



Reliably Serving
a Thirsty World



IW 215 LX



Power	
Voltage (V)	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.42A / 118W / 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (KWH/24hrs)	1.14
% lower than ES Standard	5.0%
Hot Water System	
Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On)	166.57°F / 191.43°F
Hot water ARI Rating	45 6oz > 165°F +/-10%
Hot Thermostat / Heat Limiter	203°F +/-8°F
Hot Thermostat / Thermister Cycle	167 +/- 11°F
i-Boil Set Point	N/A
Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On)	N/A
Hot Water Flow Rate	0.96 oz/sec
Hot Water Flow Rate (oz per sec)w/Accu-Temp delay	N/A
Hot Tank Size (L)	2.0L
Heat Band Wattage	450W
Cold Water System	
Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON)	45.87°F / 42.2°F
Cold Water ARI Rating	27 5oz < 50°F +/-10%
Cold Thermostat Set Point	45°F +/-8°F
Cold Water Flow Rate	1.4 oz/sec
Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay	N/A
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal)	1.0 / 0.55 / 0.4
Weights and Measurements	
Net Weight (Lbs)	34.6
Gross Weight (Lbs)	37.9
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.6x13x39.2 / 13.1x13.9x39.8
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45' HC)	518
Certifications	UL